

Technical Datasheet



Article No. 101

Article Contaclean

Available sizes

200ml, 400ml



Product description / Please note

CONTACTCLEAN cleans contacts of all types and removes oxide and sulphide layers efficiently from any metallic contact surfaces. Special inhibitors ensure long lasting lubrication and corrosion protection during the application of CONTACTCLEAN. It reduces the contact resistance that leads to failures and eliminates voltage drops. CONTACTCLEAN guarantees a durable preservation of the perfect operational reliability of all electromechanical contacts.

Application

CONTACTCLEAN can be used on all kind of switches as well as on sliding contacts of variable capacitors, contact banks and relays. Additional to its cleansing advantages, CONTACTCLEAN ensures also the maintenance of metallic surfaces in electrical engineerings. CONTACTCLEAN is used in measurement technique, telecommunication systems, data processing systems, aerospace and military. It is also particularly suitable for electronic and electric motorcar equipment. Electronical devices to be switched-off during cleaning and plug to be taken out. Cleaning instructions should to be taken into account. Further information concerning CONTACTCLEAN is available in the MSDS.

Physical Properties

Appearance	reddish liquid
Odor	characteristic
Density at 25°C	0,73 [g/cm ³]
Reduction of contact resistance	> 2 [mΩ]
Residue	oily film
Material compatibility	good
Temperature resistance	up to +80°C

Storage / Shelf life

Shelf life is 2 years if stored correctly.
Package after emptying to be disposed via metal scrap.